



Technical specifications (EN)

WiikHall Aluminium Structure 6,5 x

Framework Aluminium, Can be extended to an indefinite length in four-metre-long sections

Cover White PVC-coated polyester with extra UV protection

Doors

One lace-up fabric door 2,9 x 3 metres (w x h) at each gable

Ventilation

One air vents in each gable

Wind load capacity 0.65 Kn/sq.m

(about 31 m/s) when the building is attached to the ground in accordance with the assembly instructions

Snow load capacity 75 kg/sq.m when the building is attached to the ground in accordance with the assembly instructions

Exterior dim ~

Width	6500
Length	*
Side height	2500
Gable height	3900
Arch distance	4000

* Can be constructed in any desired length by adding 4-metre-long sections





Contact information



O.B Wiik Norge (N)

O.B.Wiik AS,
 Industriveien 13,
 2020 Skedsmokorset,
 Telefon +47 64 83 55 00
 Telefaks +47 64 83 55 01
 www.obwiik.no
 E-post obw@obwiik.no

O.B Wiik Sverige (SE)

O.B.Wiik AB,
 Borrvägen 3,
 155 93 Nykvarn
 Telefon +46 (0)8 649 80 80
 Telefaks +46 (0)8 649 80 79
 www.obwiik.se
 E-post obw@obwiik.se

O.B Wiik Denmark (DK)

O.B.Wiik AS
 Hasselvej 10
 4780 Stege
 Tlf.: +45 70 20 34 75
 Fax: +45 70 20 34 76
 www.obwiik.dk
 E-post obw@obwiik.dk

O.B Wiik International (EN)

O.B.Wiik AS,
 Industriveien 13,
 2020 Skedsmokorset,
 Telephone +47 64 83 55 00,
 Fax +47 64 83 55 01
 www.obwiik.com
 E-mail obw@obwiik.com